



TH2-stop



Ref. std ETAG 22 + ETA 19/0139
Certificate number: 0970-CPR-139

DESCRIPTION: Three-layer waterproofing membrane for application under ceramic tiles to protect floors and walls from moisture and vapour migration. Complete system with accessories.

	Reference Standard	Value	Measure Units	Toll.
Fabric				
Raw Material		PP		
Internal Core				
Raw Material (+ UV stabiliser)		LDPE		
Thickness	EN 1849-2	0,22	mm	±0,05


Composite				
Weight	EN 1849-2	275	g/m ²	±10%
Thickness 2 Kpa	EN 1849-2	0,5	mm	±10%

Physic Properties				
Water penetration / watertightness under installed conditions penetration	EN1928 B PG AIV F 3,8	1,5	(24 h no leakage)	
Water vapour transmission	ASTM E96-15 method E	0,033	gr/ft ² /hr/inHg	
Chemical Resistance in the installed conditions	EN 1847 EN 527-3	Resistant to alkali and acids		

Mechanical Properties				
Robinson Wheel test	ASTM C 627	Heavy Commercial Rating		Test Report # TJ1732, made by QAI Testing laboratory
Pull out test (cem. glue)	EN 1348	0,5	N/mm ²	±0,1

Dimensions				
Roll				
Length	-	5m or 30m	m	±0,2
Width	-	1	m	±0,1
Rolls/plt	-	154 or 40	n	

T-Bandel H 12,5 cm T-Corner E: 15 x 15 cm T-Corner I: 15 x 12,5 cm T-Wall collar : 12 x 12 cm T-Fix



The information given in this data sheet is to the best of our knowledge true and correct, however new research results and practical experience can make revisions necessary. No guarantee or liability can be drawn from the information mentioned herein. Furthermore, is not our intention to violate any patents or licences.



TeMa Technologies and Materials srl
Via dell'Industria, 21 31029 Vittorio V.to (TV) - I -
+39.0438.50.31 - Fax +39.0438.50.34.60
e-mail: info@temacorporation.com
www.temacorporation.com

mar ch 21

rev 3