# dB-Fix

**DESCRIPTION:** Acrilic glue in water dispersion, with high adhesion properties and good chemical stability. It is used to install T Silence dB on the floor.

## *Chemical-physical properties*

| | | |
|---|---|---|
| Consistancy: | water based | |
| Colour_ | white opaque | |
| Viscosity | 1000-5000 | cps |
| pH | 5-7 | |
| Solid content | 60% | |
| | | |
| | | |
| Stocking temperature: | +5°C / +40°C | |

## *Application Field*

To install T-Silence on the floor, cementitiuos, ceramized, wood and wood composites. Clean the surface and be sure always to check uality and safety of adhesion with a little sample, before installing on all the surface. Apply the glue with a paint brush or in thin lines, let the water excess evaporate for some minutes and then press the T Silence on the surface to have a good boinding- Total dry time is 5 minutes,

*The information given in this data sheet is to the best of our knowledge true and correct, however new research results and practical experience can make revisions necessary. No guarantee or liability can be drawn from the information mentioned herein. Furthermore, is not our intention to violate any patents or licences.*

**TeMa Technologies and Materials srl**
Via dell'Industria, 21 31029 Vittorio V.to (TV) - I -
Tel. +39.0438.50.31 - Fax +39.0438.50.34.60
e-mail: info@temacorporation.com
www.temacorporation.com

**Aug-18**
**Rev. 1**